

10 HP G Series Open Rotary Screw

38 cfm @ 150 psi

Basic Compressor Features

- Spin on separator
- Spin on oil filter
- Simplified operating controls
(No complicated micro-processor)
- Single control solenoid operation
- UL control components
- Alpha profile rotors
- Air/Oil cooler
- Easy to remove bolt on oil cooler
- Standard operating pressure 175 psi
- Extended oil drain for easy service
- Factory filled with premium synthetic fluid
- ASME/CRN Powder coated receiver
- Heavy duty air filter
- Automatic tank drain
- Smart contractor
- Vibration isolation pads
- Tank discharge ball valve
- Free freight in pre-paid area & southern Canada



| Model Number | Phase | Voltage | Tank | Length | Width | Height | Amp Draw 230 Volt | Amp Draw 480 Volt |
|--------------|-------|-----------------|----------------|--------|-------|--------|-------------------|-------------------|
| R101V80-GCU | 1 | 208-230 | 80 Gallon Vert | 36 | 25 | 78 | 40 | N/A |
| R103V80-GCU | 3 | 208-230/460-480 | 80 Gallon Vert | 36 | 25 | 78 | 28 | 14 |

Industrial Gold

Quality Air Compressor at a Great Price.

industrialgold.com • 1-800-531-9656 • Fax 972-352-6364

