

7.5-20 HP Portable Electric Rotary Screw


7.5hp 26 cfm @ 150 psi
 10hp 38 cfm @ 150 psi
 15hp 52 cfm @ 150 psi
 20hp 78 cfm @ 150 psi
 78-84 dba

Features

- Spin on separator
- Spin on oil filter
- Simplified operating controls
- Single control solenoid operation
- UL control components
- Alpha profile rotors
- Oil cooler
- Easy to remove bolt on cooler
- Standard operating pressure 150 psi
- Extended oil drain for easy service
- Factory Filled with premium synthetic fluid
- Heavy duty air filter
- Smart contactor
- Vibration isolation feet
- Heavy duty AG style tires
- Easy lift and roll center of gravity
- Fork lift, lifting points

Options

- Air/Oil cooler
- Discharge filter regulator
- TEFC drive motor
- NEMA 4 controls



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt	Weight
R71P8-GCU	1	208-230	8 Gallon Twin	48	29	34	32	N/A	375
R103P8-GCU	3	208-230 or 460-480	8 Gallon Twin	48	29	34	28	14	395
R153P8-GCU	3	208-230 or 460-480	8 Gallon Twin	48	29	34	42	21	400
R203P8-GCU	3	208-230 or 460-480	8 Gallon Twin	48	29	38	54	27	450

Industrial Gold
Quality Air Compressor at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 7-2017

