

Reciprocating Compressor Alternating Control Panel

Standard Features

- 2-Motor contactors
- 1-Smart relay alternating control
- 2-Control voltage fuses
- Common main incoming power connection point
- 2-Grounding lugs
- UL Certification
- CSA Certification
- Adjustable motor overload settings
- Alternates from compressors A to B1
- Selector switch to run either A or B2
- Built in timer to prevent A or B running for extended periods3
- Start delay to prevent both units from starting at the same time4
- If compressor A or B fails the other compressor continues to operate the system
- Din rail mount contactors, fuse block, smart relay

Options

- NEMA 4
- NEMA 4X
- NEMA 12
- 575 Volt
- 50HZ
- Modbus connection
- Ethernet port monitoring connection
- Remote re-set of overloads
- Control pressure switches

Panel size ranges

- 208-230 Volt 3-15hp
- 208-230 Volt 20-30hp
- 460-480 Volt 3-25hp
- 460-480 Volt 25-50hp
- 575 Volt 3-20hp



Feature Explanation

- 1** Control panel automatically alternates from compressor A to B
- 2** You can select to run just compressor A or compressor B
- 3** If compressor A runs for more than 5 minutes then panel turns compressor B on to help lower the duty cycle on compressor A (Same applies when compressor B is in lead)
- 4** Built in 10 second start delay to prevent both compressor from coming on at the same time

Industrial Gold

Quality Air Compressor at a Great Price.

industrialgold.com • 1-800-531-9656 • Fax 972-352-6364

