

10 HP Enclosed Rotary Screw

38 cfm @ 150 psi

40 cfm @ 125 psi

72 dba

Features

- Airend manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL Control components
- Automatic belt tensioning
- Omega profile rotors
- Air/Oil cooler
- Heavy duty air filter
- Easy to access oil cooler for cleaning
- Operating pressures from 100-190 psi available
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- Solid steel sound enclosure
- Vertical draft ventilation

CDR Compressor Features

- All basic features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- ASME powder coated air receiver
- Refrigerated air dryer
- Stainless Steel discharge lines
- Free freight in the 48 states & southern Canada



| Model Number | Phase | Voltage | Tank | Package | Length | Width | Height | Amp Draw 230 Volt | Amp Draw 480 Volt |
|--------------|-------|-------------|----------------------|---------|--------|-------|--------|-------------------|-------------------|
| R101ENC | 1 | 208-230 | 80 Gallon Horizontal | Basic | 32 | 28 | 42 | 44 | N/A |
| R101ENC-CDR | 1 | 208-230 | 80 Gallon Horizontal | CDR | 64 | 28 | 63 | 44 | N/A |
| R103ENC | 3 | 208-230-460 | 80 Gallon Horizontal | Basic | 32 | 28 | 42 | 28 | 14 |
| R103ENC-CDR | 3 | 208-230-460 | 80 Gallon Horizontal | CDR | 64 | 28 | 63 | 28 | 14 |

Industrial Gold

Quality Air Compressor at a Great Price.

industrialgold.com • 1-800-531-9656 • Fax 972-352-6364

