

60 HP Enclosed Rotary Screw

225 cfm @ 150 psi

245 cfm @ 125 psi

77 dba

Features

- Airend manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL Control components
- Automatic belt tensioning
- Omega profile rotors
- Air/Oil cooler
- Heavy duty air filter
- Easy to access oil cooler for cleaning
- Operating pressures from 100-190 psi available
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- Solid steel sound enclosure
- Vertical draft ventilation

CDR Compressor

Features

- All basic features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- ASME powder coated air receiver
- Refrigerated air dryer
- Stainless Steel discharge lines
- Free freight in the 48 states & southern Canada



Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
R603ENC	3	208-230-460	N/A	Basic	57	44	60	144	72
R603ENC-CDR	3	208-230-460	120 Gallon Vertical	CDR	57	44	60	144	72

Industrial Gold

Quality Air Compressor at a Great Price.

industrialgold.com • 1-800-531-9656 • Fax 972-352-6364

