

39 CFM Gas/Diesel Rotary Screw

39 cfm @ 150 psi

Features

- Airend manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL control components
- Easy to remove bolt on oil cooler for cleaning
- Operating pressures from 100-190 PSI available
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- Industrial Duty Drive engine

Platinum Compressor Features

- All basic features
- Air/Oil cooler
- SIMPLEX controls
- Vibration isolation pads
- Battery mounted and wired
- Free freight in the 48 states & southern Canada

Platinum Stainless Features

- All Platinum features
- Stainless Steel discharge lines
- Tank discharge ball valve
- Stainless Steel 12 inch install line
- First oil and filter change



Model	HP	Mount	Tank	Platinum/ Basic	Drive engine	Length	Width	Height
R18DEK30	17	Tank mount	30 Gallon Horizontal	Basic	Kohler Diesel	48	30	48
R18GEH30	18	Tank mount	30 Gallon Horizontal	Basic	Honda	48	30	48
R18GEK30	18	Tank mount	30 Gallon Horizontal	Basic	Kohler	48	30	48

Unit does not come standard with a fuel tank
Add -P to model number to make Platinum Unit

Industrial Gold

Quality Air Compressor at a Great Price.

industrialgold.com • 1-800-531-9656 • Fax 972-352-6364

