

195 CFM Hydraulic Motor Driven Enclosed Rotary Screw Compressor

195 cfm @ 100 psi

185 cfm @ 150 psi

Features

- Heavy duty industrial rotary screw airend
- Intake filter silencer
- 12 Volt compressed air & oil cooler*
- Hydraulic fluid flow regulator
- Hydraulic fluid pressure regulator
- Hydraulic fluid bypass valve
- Steel mounting plate
- External NEMA 4 on/off switch
- All hydraulic fluid and air connections 1 side
- Easy to remove compressor cover
- 12 Volt control system*
- NEMA 4 Load/Unload switch
- Compressor load/unload operation
- CAS SMART fluid control system
- Vibration mounting pads
- ASME/CRN Certified safety valves

Options

- Cover color change
- Hydraulic fluid cooler
- 24 Volt operation
- 110 Volt operation
- Cold weather heating package
- High ambient temperature cooling package
- Tank mounted
- Hose reels

Control voltage connection to be supplied by vehicle/equipment compressor is mounted to

Do not let hydraulic fluid exceed 190F

Dimensions are representatives of package dimensions not total space required for mounting



Model	CFM@100psi	CFM@150psi	Hydraulic psi required	GPM Hydraulic Flow Required	Length	Width	Height
H-BM185R	195	185	2250	55	56	38	40

Industrial Gold

Quality Air Compressor at a Great Price.

industrialgold.com • 1-800-531-9656 • Fax 972-352-6364

